

SINGLE-PHASE SERIES 3

Powerware 3105

Standby UPS (500–700 VA)

Protect your small office and home office computer and telephone equipment from the damaging threats that lurk in public utility power especially power outages, sags, and line noise.

- Save space with a compact design that fits easily under a desk or can be conveniently wall-mounted, with quick access to all surge suppression and battery backup receptacles
- Extend UPS service life with user-replaceable batteries
- Protect network-connected equipment from surges coming over LAN or telephone lines
- Be informed of power problems and low battery conditions with audible alarms
- Deliver short-term mobile power with start-on-battery capability
- Warranty (US and Canada): 2-year limited warranty, 5-year pro-rated warranty (with warranty registration), and \$25,000 load protection guarantee. Optional Gold Plans available



POWERWARE 3105 DOMESTIC MODELS: 120V, 50/60 Hz

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW3105 500	103004247-5592	500/300	1.8 meter	8 5-15R Outlets	11.0 x 7.0 x 4.4	7.94	\$79
PW3105 700	103004248-5592	700/420	Line cord with 90° 5-15P	(4 Battery Backup & 4 Surge Protection only)	11.0 x 7.0 x 4.4	9.70	\$97

POWERWARE 3105 INTERNATIONAL MODELS: 230V, 50/60 Hz

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions H x W x D (inches)	Weight (lb)	List Price
PW3105 500i	103004250-5592	500/300	IE C14 inlet,	8 IEC C13 Outlets	4.6 x 11.0 x 7.0	7.36	\$75
PW3105 700i	103004251-5592	700/420	1.8 meter line patch cord IEC to IEC	(4 Battery Backup & 4 Surge Protection only)	4.6 x 11.0 x 7.0	9.17	\$102

SOFTWARE

Powerware LanSafe® software is included free of charge. See the software and connectivity product section for more detail.

SERVICE PLANS

For service plans, please see the service section beginning on page 86.

POWERWARE 3105 BATTERY BACKUP TIMES (in minutes)

UPS model									
Load (VA)	50W	100W	150W	200W	250W	300W	350W	400W	
500	43	17	11	6	4	3			
700	53	30	14	9	7	6	4	3	

Note: Battery runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc.