

SINGLE-PHASE SERIES 5

Powerware 5110

Line-interactive UPS (500–1500 VA)

Protect your small office and home office computer and telephone equipment from the damaging threats that lurk in public utility power.

- Protect small office and home office equipment from power outages, surges, sags, and line noise
- Save space with a compact design that fits easily under a desk, mounted under a computer terminal, or on a computer shelf with quick access to all receptacles
- Keep essential systems running through power outages by plugging them into receptacles with surge suppression and battery backup
- Conserve battery runtime by plugging non-essential equipment into receptacles that have surge suppression only
- Extend UPS service life with user-replaceable batteries
- Protect network-connected equipment from surges coming over LAN or telephone lines
- USB Port and cables are standard
- Be informed of power problems and low battery conditions with audible alarms
- Deliver short-term mobile power with start-on-battery capability
- Warranty (US and Canada): 2-year limited warranty, 5-year pro-rated warranty (with warranty registration), and \$150,000 load protection guarantee. Optional Gold Plans available



POWERWARE 5110 DOMESTIC MODELS: 120V, 50/60 Hz

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW5110 500	103004256-5591	500/300	1.8 meter	8 5-15R Outlets	10.6 x 3.4 x 10.2	12.1	\$120
PW5110 700	103004257-5591	700/420		Line cord	(4 Battery Backup & Surge Protection;	10.6 x 3.4 x 10.2	15.2
PW5110 1000	103004258-5591	1000/600	with	Surge Protection;	10.6 x 3.4 x 15.1	28.0	\$212
PW5110 1500	103004259-5591	1440/900	90 deg. 5-15P	4 Surge Protection only)	10.6 x 3.4 x 15.1	29.1	\$240

POWERWARE 5110 INTERNATIONAL MODELS: 230V, 50/60 Hz

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions H x W x D (inches)	Weight (lb)	List Price
PW5110 500i	103004261-5591	500/300	IEC C14 inlet,	8 IE C13 Outlets	10.2 x 3.4 x 10.6	13.4	\$125
PW5110 700i	103004262-5591	700/420	1.8 meter	(4 Battery Backup & Surge Protection;	10.2 x 3.4 x 10.6	16.5	\$155
PW5110 1000i	103004263-5591	1000/600	line patch cord	Surge Protection;	10.6 x 3.4 x 15.1	29.1	\$217
PW5110 1500i	103004264-5591	1500/900	IEC to IEC	4 Surge Protection only)	10.6 x 3.4 x 15.1	30.2	\$245

SOFTWARE

Powerware LanSafe software is included free of charge. See the software and connectivity product section for more detail.

SERVICE PLANS

For service plans, please see the service section beginning on page 81.

POWERWARE 5110 BATTERY BACKUP TIMES (in minutes)

Load (VA)	100W	200W	300W	400W	500W	600W	700W	800W	900W
500	17	6	3						
700	30	9	6	3					
1000	64	28	17	12	8	5			
1500	74	35	20	14	10	7	6	5	4

Note: Battery runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SINGLE-PHASE SERIES 5

Powerware 5115

Line-interactive UPS (500–1400 VA)

The Powerware 5115 offers Series 5 advanced protection for PCs, small-office-home-office equipment, workstations, and small networking devices.

- ABM technology significantly increases battery service life
- Pure sine wave output delivers smooth, continuous power
- Buck and Boost voltage regulation corrects incoming voltage fluctuations
- Hot-swappable batteries simplify service
- Network Transient Protector isolates network/phone wiring
- Software Suite CD bundle provides monitoring and shutdown capabilities
- Warranty (US and Canada): 2-year limited warranty. 10-year pro-rated warranty (with warranty registration), and \$150,000 load protection guarantee. Optional Gold Plans available.



POWERWARE 5115 DOMESTIC TOWER MODELS: 120V, 50/60 Hz¹

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions (H x W x D inches)	Weight (lb)	List Price
PW5115 500	05146548-5591	500/320	5-15P	(4) 5-15R	7.6 x 5.9 x 10.6	17.2	\$220
PW5115 750	05146554-5591	750/500	5-15P	(4) 5-15R	7.6 x 5.9 x 13.2	27.3	\$319
PW5115 1000	05146560-5591	1000/670	5-15P	(6) 5-15R	15.1 x 5.9 x 13.2	27.8	\$448
PW5115 1400	05146566-5591	1400/950	5-15P	(6) 5-15R	15.1 x 5.9 x 15.4	37.0	\$554

1. Bundled with Software Suite CD and communication cable (DB9f to DB9m P/N 60420064-002).

POWERWARE 5115 INTERNATIONAL TOWER MODELS: 230V, 50/60 Hz¹

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions H x W x D (inches)	Weight (lb)	List Price
PW5115 500i	05146549-5591	500/320	IEC-320-C14	(4) IEC-320-C13	7.6 x 5.9 x 10.6	17.2	\$220
PW5115 750i	05146555-5591	750/500	IEC-320-C14	(4) IEC-320-C13	7.6 x 5.9 x 13.2	27.3	\$319
PW5115 1000i	05146561-5591	1000/670	IEC-320-C14	(6) IEC-320-C13	7.6 x 5.9 x 13.2	27.8	\$448
PW5115 1400i	05146567-5591	1400/950	IEC-320-C14	(6) IEC-320-C13	7.6 x 5.9 x 15.4	37.0	\$554

1. Bundled with Software Suite CD and communication cable (DB9f to DB9m P/N 60420064-002).

SOFTWARE

Powerware LanSafe software is included free of charge. See the software and connectivity product section for more detail.

SERVICE PLANS

For service plans, please see the service section beginning on page 81.

POWERWARE 5115 BATTERY BACKUP TIMES (in minutes)

Load (VA/Watts)	PW5115 500	PW5115 750	PW5115 1000	PW5115 1400
200/128	17	38	41	58
300/192	11	27	28	41
500/320	5	14	15	28
600/402	–	9	10	19
750/503	–	6	8	14
900/603	–	–	6	10
1000/670	–	–	5	8
1200/804	–	–	–	6
1400/938	–	–	–	5

Note: Runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SINGLE-PHASE SERIES 5

Powerware 5115 Rackmount

Line-interactive UPS (500–1500 VA)

The Powerware 5115 rackmount UPS offers high-density, Series 5 advanced protection for servers, storage systems, network equipment, and other critical devices.



- 1U rack height conserves valuable rack space for other critical devices while delivering powerful performance
- Unique chassis design adapts to 19-inch rack, wall-mount, side-cabinet (zero U), and bench-top applications
- ABM technology significantly increases battery service life
- True sine wave output delivers smooth, continuous power
- Load segments enable scheduled shutdowns and extend backup time for critical devices
- Hot-swappable batteries minimize downtime
- Standard USB and RS-232 serial port extend communication capacity; X-Slot® options available
- Bundled software package provides UPS power management, monitoring and automatic shutdown
- Warranty (US and Canada): 2-year limited warranty. 10-year pro-rated warranty (with warranty registration), and \$150,000 load protection guarantee. Optional Gold Plans available.

POWERWARE 5115 DOMESTIC RACKMOUNT MODELS: 120V, 50/60 Hz¹

Model	Part Number	Power Out (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW5115 500 RM	103003266-6591	500/320	5-15P	(4) 5-15R	1.75 x 17.3 x 22.8	35.2	\$306
PW5115 750 RM	103003269-6591	750/520	5-15P	(4) 5-15R	1.75 x 17.3 x 22.8	41.4	\$483
PW5115 1000 RM	103003272-6591	1000/670	5-15P	(4) 5-15R	1.75 x 17.3 x 22.8	41.4	\$660
PW5115 1500 RM	103003275-6591	1440/1000	5-15P	(4) 5-15R	1.75 x 17.3 x 22.8	48.6	\$820

1. Includes all mounting hardware. Bundled with Software Suite CD and communication cable (DB9f to DB9m, P/N 60420064-002).

POWERWARE 5115 INTERNATIONAL RACKMOUNT MODELS: 230V, 50/60 Hz¹

Model	Part Number	Power Out (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW5115 500i RM	103003267-6591	500/320	IEC-320-C14	(4) IEC-320-C13	1.75 x 17.3 x 22.8	35.2	\$306
PW5115 750i RM	103003270-6591	750/520	IEC-320-C14	(4) IEC-320-C13	1.75 x 17.3 x 22.8	41.4	\$483
PW5115 1000i RM	103003273-6591	1000/670	IEC-320-C14	(4) IEC-320-C13	1.75 x 17.3 x 22.8	41.4	\$660
PW5115 1500i RM	103003276-6591	1500/1000	IEC-320-C14	(4) IEC-320-C13	1.75 x 17.3 x 22.8	48.6	\$820

1. Includes all mounting hardware. Bundled with Software Suite CD and communication cable (DB9f to DB9m, P/N 60420064-002).

POWERWARE POWER DISTRIBUTION UNIT (PDU)

For a list of Powerware PDU models, refer to that section.

POWERWARE ENCLOSURE

See the Powerware Enclosure section for a comprehensive list of IT enclosure offerings.

SOFTWARE AND CONNECTIVITY OPTIONS

Bundled with Software Suite CD and communication cable. See the software and connectivity product section for more detail.

SERVICE PLANS

For service plans, please see the service section beginning on page 81.

POWERWARE 5115 RACKMOUNT BATTERY BACKUP TIMES (in minutes)

Load (VA/Watts)	PW5115 RM 500	PW5115 RM 750	PW5115 RM 1000	PW5115 RM 1500
200/130	19	37	41	76
300/190	11	25	29	58
500/320	5	13	15	28
750/520		6	8	16
900/600			6	11
1000/670			5	9
1200/800				8
1440/1000				5

Note: Backup times are approximate and may vary with equipment, configuration, battery age, temperature etc.

SINGLE-PHASE SERIES 5

Powerware 5125 Tower

Line-interactive UPS (1000–2200 VA)

The Powerware 5125 delivers cost-effective power protection for PCs, workstations, and servers.

- ABM technology significantly increases battery service life
- Buck and Double Boost voltage regulation corrects voltage fluctuations and delivers pure sine wave output
- Extended runtime capability with Extended Battery Modules (EBMs)
- Load segments maximize runtime for critical devices
- Hot-swappable batteries simplify service
- Warranty (US and Canada): 2-year limited warranty. 10-year pro-rated warranty (with warranty registration), and \$150,000 load protection guarantee. Optional Gold Plans available.



POWERWARE 5125 DOMESTIC TOWER MODELS: 120V, 50/60 Hz

Model	Part Number	Power Out (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW5125 1000	05146629-5591	1000/700	5-15P	(6) 5-15R	9.45 x 6.38 x 15.79	34.3	\$481
PW5125 1500	05146632-5591	1440/1050	5-15P	(6) 5-15R	9.84 x 6.38 x 18.39	50.7	\$634
PW5125 2200	05146635-5591	1920/1600	5-20P	(6) 5-15R, (2) 5-20R	9.84 x 8.07 x 19.41	68.3	\$948

208V Model

PW5125 2200b	05146636-5591	2080/1600	IEC-320, 15A inlet	(9) IEC-320-C13	9.84 x 8.07 x 19.41	68.3	\$1,234
--------------	---------------	-----------	--------------------	-----------------	---------------------	------	---------

POWERWARE 5125 INTERNATIONAL TOWER MODELS: 230V, 50/60 Hz - includes (2) IEC interconnect cables

Model	Part Number	Power Out (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW5125 1000i	05146630-5591	1000/700	IEC-320-C14	(6) IEC-320-C13	9.45 x 6.38 x 15.79	34.3	\$481
PW5125 1500i	05146633-5591	1500/1050	IEC-320-C14	(6) IEC-320-C13	9.84 x 6.38 x 18.39	50.7	\$634
PW5125 2200i	05146637-5591	2200/1600	IEC-320-C14	(9) IEC-320-C13	9.84 x 8.07 x 19.41	68.3	\$948

POWERWARE 5125 OPTIONS

Description	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Extended Battery Modules				
PW5125 24V EBM (for 1000 Tower)	05146638-5591	9.84 x 6.38 x 18.66	59.5	\$419
PW5125 48V EBM (for 1500/2200 Tower)	05146639-5591	9.84 x 6.38 x 18.66	59.5	\$433

SOFTWARE AND CONNECTIVITY OPTIONS

Bundled with Software Suite CD and communication cable. See the software and connectivity product section for more detail.

SERVICE PLANS

For service plans, please see the service section beginning on page 81.

POWERWARE 5125 TOWER BATTERY BACKUP TIMES (in minutes full load/half load)*

Load (VA)	Standard Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
1000	5/14	25/60	55/170	83/199	109/228
1500	6/17	33/79	63/146	92/174	120/201
2200	5/14	26/60	55/170	81/198	106/224

*Up to 4 EBMs can be connected to the 1000-2200 VA models. EBM runtimes include internal batteries. Runtime chart provides typical information. Battery backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SINGLE-PHASE SERIES 5

Powerware 5125 Rack/Tower

Line-interactive UPS (1000-3000 VA)

The Powerware 5125 delivers cost-effective power protection for PCs, workstations, and servers.

- ABM technology significantly increases battery service life
- Buck and Double Boost voltage regulation corrects voltage fluctuations and delivers pure sine wave output
- Extended runtime capability with Extended Battery Modules (EBMs)
- Load segments maximize runtime for critical devices
- Hot-swappable batteries simplify service
- Space saving 2U rack height (1000-3000 VA)
- Warranty (US and Canada): 2-year limited warranty, 10-year pro-rated warranty (with warranty registration), and \$150,000 load protection guarantee. Optional Gold Plans available.



POWERWARE 5125 DOMESTIC RACK/TOWER MODELS: 120V, 50/60 Hz

Model	Part Number	Power Out (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW5125 1000 RM	05146666-6501	1000/900	5-15P	(6) 5-15R	3.5 (2U) x 17.0 x 19.4	61.0	\$777
PW5125 1500 RM	05146669-6501	1440/1340	5-15P	(6) 5-15R	3.5 (2U) x 17.0 x 19.4	61.0	\$998
PW5125 2400 RM	05147564-6501	2400/2250	L5-30P	(1) L5-30R, (6) 5-15R	3.5 (2U) x 17.3 x 24.5	89.0	\$1,420
PW5125 3000 RM	05147152-6501	2880/2700	L5-30P	(1) L5-30R, (6) 5-15R	3.5 (2U) x 17.3 x 24.5	89.0	\$1,637

POWERWARE 5125 INTERNATIONAL RACK/TOWER MODELS: 230V, 50/60 Hz;

includes (2) IEC interconnect cables

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacle	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW5125 1000i RM	05146667-6591	1000/900	IEC-320-C14	(6) IEC-320-C13	3.5 (2U) x 17.0 x 19.4	61.0	\$810
PW5125 1500i RM	05146670-6591	1500/1340	IEC-320-C14	(6) IEC-320-C13	3.5 (2U) x 17.0 x 19.4	61.0	\$1,031
PW5125 2400i RM	05147565-6591	2400/2250	IEC-309, 16A Plug (12' attached)	(9) IEC-320-C13, (1) IEC-320-C19	3.5 (2U) x 17.3 x 24.5	89.0	\$1,430
PW5125 3000i RM	05147154-6501	3000/2700	IEC-309, 16A Plug (12' attached)	(1) IEC-320-16A (C19), (9) IEC-320-10A (C13)	3.5 (2U) x 17.3 x 24.5	89.0	\$1,637
PW5125 3000g RM*	05147155-6591	3000/2700	IEC-320-C20 inlet	(9) IEC-320-C13, (1) IEC-320-C19	3.5 (2U) x 17.3 x 24.5	89.0	\$1,694
PW5125 3000e RM	05147641-6591	3000/2700	IEC-320-C20 inlet	(9) IEC-320-C13, (1) IEC-320-C19	3.5 (2U) x 17.3 x 24.5	89.0	\$1,637

*PW5125 3000g RM Model input/output voltage is 200/240V. 8-ft. cord with L6-20P is available. Part number is 152507429-010. List price is \$100.
Note: rail kit not included.

POWERWARE 5125 OPTIONS

Description	Part Number	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PowerPass® Distributing Module						
700-1500 VA, 120V	05146519-001	5-15P	(6) 5-15R & (1) 5-15R for laser printer (surge only)	3.5 x 11.0 x 4.5	2.5	\$249
Extended Battery Modules						
PW5125 48V EBM RM (for 1000/1500 RM)	05147148-6591			3.5 (2U) x 17.0 x 19.4	65.0	\$659
PW5125 120V EBM RM (for 2400/3000 RM)	05147156-6591			3.5 (2U) x 17.0 x 24.5	121.0	\$1,245

Notes: PW9125 EBMs are compatible with PW5125 UPS models. Up to 4 EBMs can be connected to the UPS.

Optional Rack Mounting Hardware

4-Post Rail Kit (for 1000-3000 VA Models)	05141562-0091			Fits 19-inch racks		\$103
2-Post Rail Kit (for 1000-3000 VA Models)	05146726-5591			Fits 19-inch racks		\$105
3-Slot Seismic Mounting Kit (for 1000/1500 2-in-1 models)	05146871-5501					\$519
5-Slot Seismic Mounting Kit (for 1000/1500 2-in-1 models)	05146875-5501					\$569

SINGLE-PHASE SERIES 5

Powerware 5125 Rack/Tower *(continued)*

POWERWARE POWER DISTRIBUTION UNIT (PDU)

For a list of Powerware PDU models, refer to that section.

POWERWARE ENCLOSURE

See the Powerware Enclosure section for a comprehensive list of IT enclosure offerings.

SOFTWARE AND CONNECTIVITY OPTIONS

Bundled with Software Suite CD and communication cable. See the software and connectivity product section for more detail.

SERVICE PLANS

For service plans, please see the service section beginning on page 81.

POWERWARE 5125 RACK/TOWER BATTERY BACKUP TIMES (in minutes full load/half load)*

Load (VA)	Standard Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
1000	7/19	33/68	58/120	82/166	105/214
1500	5/13	23/57	49/161	73/172	96/205
2400	7/19	35/73	60/124	85/177	110/229
3000	5/15	25/61	49/103	69/146	90/190

*Up to 4 EBMs can be connected to the 1000-3000 VA models. EBM runtimes include internal batteries. This chart provides typical information. Battery backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SINGLE-PHASE SERIES 5

Powerware 5125 Rackmount

Line-interactive UPS (5000-6000 VA)

The Powerware 5125 delivers a space-saving 3U rack height package and is the ideal high-density power protection solution for your servers, storage systems, network equipment and other critical devices

- ABM technology significantly increases battery service life
- Load segment control (separate receptacles groups) enables scheduled shut downs and maximum runtime for each critical device
- Communication bay allows for optional communication cards for remote management; USB and serial ports extend capacity
- Hot-swappable battery and electronics modules simplify service, provide high availability and faster mean time to repair
- Warranty (US and Canada): 2-year limited warranty, 10-year pro-rated warranty (with warranty registration), and \$150,000 load protection guarantee. Optional Gold Plans available.



POWERWARE 5125 RACKMOUNT MODELS: 200-240V

Weight Model	Part List Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	Price
PW5125 5000	103003611-5591	5000/4500	L6-30P	L6-30R on short cord (2) L6-20, (4) C13	5.25 (3U) x 17.50 x 26.0	161.0	\$2,963
PW5125 6000 HW	103003610-5591	6000/5400	Hardwired	Hardwired (4) C19, (4) C13	5.25 (3U) x 17.50 x 26.0	161.0	\$3,258
PW5125 6000i	103003612-5591	6000/5400	IEC-309-32A	IEC-309-32A on short cord (4) C19, (4) C13	5.25 (3U) x 17.50 x 26.0	161.0	\$3,258

POWERWARE 5125 RACKMOUNT MODELS WITH FACTORY-INSTALLED CONNECTUPS WEB/SNMP CARD

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PW5125 5000 Web	103003611-5597	5000/4500	L6-30P	L6-30R on short cord, (2) L6-20 (4) C13	5.25 (3U) x 17.50 x 26.0	161.0	\$3,139
PW5125 6000 HW Web	103003610-5597	6000/5400	Hardwired	Hardwired, (4) C19, (4) C13	5.25 (3U) x 17.50 x 26.0	161.0	\$3,423
PW5125 6000i Web	103003612-5597	6000/5400	IEC-309-32A	IEC-309-32A on short cord, (4) C19, (4) C13	5.25 (3U) x 17.50 x 26.0	161.0	\$3,423

Notes: UPS models ship with both black and beige front panels. UPS models include rail kits and mounting hardware. Output receptacles divided into two load segments.

POWERWARE 5125 RACKMOUNT OPTIONS

Model	Part Number	Power Out (VA/Watt)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PowerPass Distribution Modules							
5000VA PPDM	103004652-5501	5000/4500	L6-30P	1ea L5-30R	5.25 x 17.50 x 26.0 UPS	161.0	\$3,666
				2ea L6-20R 8ea 5-15R, 4ea IEC-320-C13	5.25 x 17.37 x 24.8 PPDM	106.0	
5000VA PPDM	103004652-5503	5000/4500	L6-30P	2ea L6-20R	5.25 x 17.50 x 26.0 UPS	161.0	\$4,015
				20ea 5-15R	5.25 x 17.37 x 24.8 PPDM	106.0	
				4ea IEC-320-C13	1.65 x 17.0 x 8.0	11.0	
Model	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price			
Extended Battery Modules							
PW9125 240V EBM (Beige)	103003387-5591	5.25 (3U) x 17.50 x 26.0	169.0	\$1,297			
PW9125 240V EBM (Black)	103003387-6591	5.25 (3U) x 17.50 x 26.0	169.0	\$1,297			

EBM Notes: EBMs are the same EBMs used for the Powerware 9125 5000/6000 VA product line.

SINGLE-PHASE SERIES 5

Powerware 5125 Rackmount *(continued)*

POWERWARE POWER DISTRIBUTION UNIT (PDU)

For a list of Powerware PDU models, refer to that section.

POWERWARE ENCLOSURE

See the Powerware Enclosure section for a comprehensive list of IT enclosure offerings.

SOFTWARE AND CONNECTIVITY OPTIONS

Bundled with Software Suite CD and communication cable. See the software and connectivity product section for more detail.

SERVICE PLANS

For service plans, please see the service section beginning on page 81.

POWERWARE 5125 RACKMOUNT BATTERY BACK UP TIMES (in minutes)

Load (VA/Watts)	Standard				
	Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
1000/900	59	169	303	452	612
2000/1800	26	79	138	204	274
2200/1980	21	65	112	164	223
2500/2250	19	61	106	156	210
2700/2430	17	52	89	132	180
3000/2700	15	49	85	125	168
3500/3150	13	43	73	110	142
4500/4050	8	27	52	76	102
5000/4500	7	24	46	67	89
5500/4950	6	22	42	61	81
6000/5400	5	19	36	53	71

Note: Backup times are approximate and may vary with equipment, configuration, battery age, temperature etc.